

MiTek Series	Nailer Size	Fastener Schedule ⁴					DF/SP		S-P-F	
		Header			Joist		Allowable Loads (Lbs.) ³		Allowable Loads (Lbs.) ³	
		Top Qty	Face Qty	Type	Qty	Type	Download ² 100%	Uplift ¹ 160%	Download ² 100%	Uplift ¹ 160%
BPHA	2X	6	--	10d x 1-1/2	8	10d x 1-1/2	2170	405	1825	340
	3X	6	2	16d x 2-1/2	8	10d x 1-1/2	3370	845	2830	710
	(2) 2X	6	4	10d	8	10d x 1-1/2	2620	1155	2200	970
	4X	6	4	16d	8	10d x 1-1/2	4005	1155	3045	970

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Listed download shall not be increased.

3) Values in the table apply to standard top mount hangers without slope, skew or any other specialty options.

4) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long, 16d x 2-1/2 nails are 0.162" dia. x 2-1/2" long.