

MiTek Series	Nailer Size	Fastener Schedule ³					DF/ SP		SPF	
		Nailer			Joist		Allowable Loads (Lbs.) ^{2,3}		Allowable Loads (Lbs.) ^{2,3}	
		Top Qty	Face Qty	Type	Qty	Type	Download 100%	Uplift ¹ 160%	Download 100%	Uplift ¹ 160%
TFL	2X	4	2	10d x 1-1/2	2	10d x 1-1/2	1270	130	1090	110
	3X	4	2	16d x 2-1/2	2	10d x 1-1/2	1600	130	1260	110
	(2) 2X	4	2	10d	2	10d x 1-1/2	1280	130	1100	110
	4X	4	2	16d	2	10d x 1-1/2	1745	130	1260	110
THO	2X	4	2	10d x 1-1/2	2	10d x 1-1/2	1235	230	950	195
	3X	4	2	16d x 2-1/2	2	10d x 1-1/2	1235	230	950	195
	(2) 2X	4	2	16d x 2-1/2	2	10d x 1-1/2	1235	230	950	195
	4X	4	2	16d	2	10d x 1-1/2	1235	230	950	195
THO (Double)	2X	4	2	10d x 1-1/2	2	10d x 1-1/2	1455	230	1250	195
	3X	4	2	16d x 2-1/2	2	10d x 1-1/2	2335	230	1815	195
	(2) 2X	4	2	10d	2	10d x 1-1/2	2370	230	1815	195
	4X	4	2	16d	2	10d x 1-1/2	2525	230	1815	195
TFI	2X	4	2	10d x 1-1/2	2	10d x 1-1/2	1985	215	1665	180
	3X	4	6	16d x 2-1/2	2	10d x 1-1/2	2715	215	2075	180
	(2) 2X	4	6	10d	2	10d x 1-1/2	2715	215	2075	180
	4X	4	2	16d	2	10d x 1-1/2	2560	215	2075	180
	4X	4	6	16d	2	10d x 1-1/2	2715	215	2075	180

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Listed loads shall not be increased.

3) Values in the table apply to standard top mount hangers without slope, skew or any other specialty options.

4) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long, 16d x 2-1/2 nails are 0.162" dia. x 2-1/2" long.