

MiTek Stock No.	Ref. No.	Steel Gauge	Dimensions (in)			Qty of CJHQs ³	Recommended Joist Size	Fastener Schedule ²				DF/SP Allowable Loads (Lbs.)				S-P-F Allowable Loads (Lbs.)			
			W	H	D			Header		Joist		Allowable Loads (Lbs.)				Allowable Loads (Lbs.)			
								Qty	Type	Qty	Type	Floor	Roof		Uplift ¹	Floor	Roof		Uplift ¹
												100%	115%	125%	160%	100%	115%	125%	160%
CJHQ6-TZ	CJT3Z	12	1-13/16	5-7/16	2-3/4	1	4x 6	6	CCWS3	6	CCWS3	1775	2040	2090	2090	1435	1650	1650	1650
						2	6 x 8	12		10		2955	2955	2955	2955	2330	2330	2330	2330
CJHQ8-TZ	CJT4Z	12	1-13/16	6-7/16	2-3/4	1	4 x 8	8	CCWS3	8	CCWS3	2370	2725	2960	3040	1915	2205	2395	2405
						2	6 x 8	16		12		3550	4085	4440	4580	2875	3305	3590	3620
CJHQ10-TZ	CJT5Z	12	1-13/16	8-7/16	2-3/4	1	4 x 10	10	CCWS3	10	CCWS3	2960	3405	3700	4415	2395	2755	2995	3495
						2	6 x 10	20		16		4735	5445	5920	6025	3830	4405	4770	4770
CJHQ12-TZ	CJT6Z	12	1-13/16	9-7/16	2-3/4	1	4 x 12	12	CCWS3	12	CCWS3	4750	5285	5285	5285	4080	4205	4205	4205
	HCJTZ					2	6 x 12	24		18		8065	8275	8275	8275	6525	6580	6580	6580

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) MiTek's CCWS3 (1/4" dia. x 3" long) structural wood screws are included with CJHQ joist hangers.

3) Maximum joist width for a standard single installation is 4".